

Choose the right tool for the job.

| EXPERT SERIES | PROFESSIONAL SERIES | PERFORMANCE SERIES |
|---------------|---------------------|--------------------|
|---------------|---------------------|--------------------|

Engineers, R&D professionals and advanced thermographers who require premium image quality and an unsurpassed level of detail in every infrared image.

Professional in-house, contract and service thermographers who need quality images and advanced features and specifications for use in multiple applications.

Technicians and contractors who need quality images and feature rich affordability for quick scans and/or intermittent inspections.

Where used

- Industrial maintenance
- Oil and gas predictive maintenance
- Power generation/transmission
- Research and development
 - Electrical
 - Mechanical
 - Biology/sciences
- Quality control
- Plus the industries included under the professional and performance series

- Industrial maintenance
- Heavy commercial facility maintenance
- Oil and gas maintenance
- Veterinary
- Reliability inspections (PdM)
- Heavy building diagnostics
 - Building envelope
 - Construction defects
- Electrical, water, gas utilities
- Chemical processing
- Machinery, instrumentation and appliances
- Plus the industries included under the performance series

- Electrical inspections
- HVAC/R inspections
- Mechanical
- Residential home inspections
- Light commercial maintenance
 - Building diagnostics
 - Building envelope
 - Commercial/industrial facilities



| | TiX1000 | TiX660 | TiX640 | TiX620 | TiX580 | TiX560 | TiX520 | TiX500 | Ti480 | Ti450 | Ti400 | Ti300 | TiS75 | TiS65/60 | TiS55/50 | TiS45/40 | TiS20 | TiS10 |
|-------------------------------|--|--|---|--|---------------------------------------|--|---------------------------------------|---------------------------------------|--|--|--|---------------------------------------|---------------------------------------|---------------------------------------|--------------------------------------|--------------------------------------|-------------------------------------|--------------------------------------|
| Detector resolution | 1024 x 768, 2048 x 1536 SuperRes. | 640 x 480, 1280 x 960 SuperRes. | 640 x 480, 1280 x 960 SuperRes. | 640 x 480, 1280 x 960 SuperRes. | 640 x 480, 1280 x 960 SuperRes. | 320 x 240, 640 x 480 SuperRes. | 320 x 240, 640 x 480 SuperRes. | 320 x 240, 640 x 480 SuperRes. | 640 x 480, 1280 x 960 SuperRes. | 320 x 240, 640 x 480 SuperRes. | 320 x 240 | 240 x 180 | 320 x 240 | 260 x 195 | 220 x 165 | 160 x 120 | 120 x 90 | 80 x 60 |
| Spatial resolution | 0.6 mRad | 0.8 mRad | 0.8 mRad | 0.85 mRad | 0.93 mRad | 1.31 mRad | 1.31 mRad | 1.31 mRad | 0.93 mRad | 1.31 mRad | 1.31 mRad | 1.75 mRad | 2.0 mRad | 2.4 mRad | 2.8 mRad | 3.9 mRad | 5.2 mRad | 7.8 mRad |
| Field of view | 32.4° x 24.7° | 30.9° x 23.1° | 30.9° x 23.1° | 32.7° x 24.0° | 34° x 24° | 24° x 17° | 24° x 17° | 24° x 17° | 34° x 24° | 24° x 17° | 24° x 17° | 24° x 17° | 35.7° x 26.8° | 35.7° x 26.8° | 35.7° x 26.8° | 35.7° x 26.8° | 35.7° x 26.8° | 35.7° x 26.8° |
| Distance to spot | 1765:1 | 1200:1 | 1200:1 | 1100:1 | 1065:1 | 753:1 | 753:1 | 753:1 | 1065:1 | 753:1 | 753:1 | 565:1 | 504:1 | 409:1 | 346:1 | 252:1 | 189:1 | 126:1 |
| Thermal sensitivity* | 50 mK | 30 mK | 30 mK | 40 mK | 50 mK | 30 mK | 40 mK | 50 mK | 50 mK | 30 mK | 50 mK | 50 mK | 80 mK | 80 mK | 80 mK | 90 mK | 100 mK | 150 mK |
| Temperature range | -40 °C to +1200 °C (-40 °F to +2192 °F) ¹ | -40 °C to +1200 °C (-40 °F to +2192 °F) ¹ | -40 °C to +1200 °C (-40 °F to +2192 °F) | -40 °C to +600 °C (-40 °F to +1112 °F) | -20 °C to +800 °C (-4 °F to +1472 °F) | -20 °C to +1200 °C (-4 °F to +2192 °F) | -20 °C to +850 °C (-4 °F to +1562 °F) | -20 °C to +650 °C (-4 °F to +1202 °F) | ≤ -20 °C to +800 °C (-4 °F to 1472 °F) | -20 °C to +1200 °C (-4 °F to +2192 °F) | -20 °C to +1200 °C (-4 °F to +2192 °F) | -20 °C to +650 °C (-4 °F to +1202 °F) | -20 °C to +550 °C (-4 °F to +1022 °F) | -20 °C to +550 °C (-4 °F to +1022 °F) | -20 °C to +450 °C (-4 °F to +842 °F) | -20 °C to +350 °C (-4 °F to +662 °F) | 20 °C to +350 °C (-4 °F to +662 °F) | -20 °C to +250 °C (-4 °F to +482 °F) |
| Focus systems | LS, AF, AMF, ES | LS, AF, AMF, ES | AF, AMF, ES | AF, AMF, ES | MSF, LS, AMF | MSF, LS, AMF | MSF, LS, AMF | MSF, LS, AMF | MSF, LS, AMF | MSF, LS, AMF | LS, AMF | LS, AMF | MF | MF (TiS65), FF (TiS60) | MF (TiS55), FF (TiS50) | MF (TiS45), FF (TiS40) | FF | FF |
| Laser distance meter | Yes | Yes | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | - | - | - | - | - | - |
| Image enhancement | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP, SR | IRF, PIP | IRF, PIP | IRF, PIP | IRF, PIP | IRF, PIP | IRF, PIP | IRF | - |
| Annotation | VA, TA | VA, TA | VA, TA | VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA, TA | IRPN, VA | IRPN, VA | IRPN, VA | VA | - | - |
| Standard video rec. | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | - | - | - | - |
| Radiometric video rec. | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | - | - | - | - |
| Optional lenses | 7 | 7 | 7 | 2 | 2 | 4 | 4 | 4 | 2 | 3 | 3 | 3 | - | - | - | - | - | - |

AF: Auto focus | **AMF:** Advanced manual focus | **ES:** EverSharp multifocal recording | **FF:** Fixed Focus | **IRF:** IR Fusion® Auto Blend | **IRPN:** IR-PhotoNotes™ | **LS:** LaserSharp® Auto Focus System
MF: Manual focus | **MSF:** MultiSharp™ Focus | **PIP:** Picture-in-Picture | **SR:** SuperResolution | **TA:** Text Annotation | **VA:** Voice Annotation

*Best possible

Compare Fluke thermal imager models

| | Expert Series Thermal Imagers | | | | | | | Professional Series Thermal Imagers | | | | Performance Series Thermal Imagers | | | | | | |
|--|--|---|---|---|--|---|--|---|---|---|---|--|--|---|---|---|---|---|
| | TiX1000 | TiX660 | TiX640 | TiX620 | TiX580 | TiX560 | TiX520 | TiX500 | Ti480 | Ti450 | Ti400 | Ti300 | TiS75 | TiS65/60 | TiS55/50 | TiS45/40 | TiS20 | TiS10 |
| IFOV (spatial resolution) | 0.6 mRad | 0.8 mRad | 0.8 mRad | 0.85 mRad | 0.93 mRad | 1.31 mRad | | | 0.93 mRad | 1.31 mRad | | 1.75 mRad | 2.0 mRad | 2.4 mRad | 2.8 mRad | 3.9 mRad | 5.2 mRad | 7.8mRad |
| Detector resolution | 1024 x 768 (786,432 pixels) SuperResolution mode: 2048 x 1536 (3,145,728 pixels) | 640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1,228,800 pixels) | 640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1,228,800 pixels) | 640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1,228,800 pixels) | 640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1,228,800 pixels) | 320 x 240 (76,800 pixels) SuperResolution mode: 640 x 480 (307,200 pixels) | | | 640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1,228,800 pixels) | 320 x 240 (76,800 pixels) SuperResolution mode: 640 x 480 (307,200 pixels) | 320 x 240 (76,800 pixels) | 240 x 180 (43,200 pixels) | 320 x 240 (76,800 pixels) | 260 x 195 (50,700 pixels) | 220 x 165 (36,300 pixels) | 160 x 120 (19,200 pixels) | 120 x 90 (10,800 pixels) | 80 x 60 (4,800 pixels) |
| Field of view | 32.4° H x 24.7° V | 30.9° H x 23.1° V | | 32.7° H x 24.0° V | 34° H x 24° V | | 24° H x 17° V | | 34° H x 24° V | | 24° H x 17° V | | 35.7° H x 26.8° V | | | | | |
| Optional lenses | 2 wide angle, 2 telephoto, 3 macro and 1 standard | | | 1 wide angle and 1 telephoto | Pre-calibrated smart optional lenses: wide angle, 2x telephoto | | Pre-calibrated smart optional lenses: wide angle, 2x and 4x telephoto, 25 micron macro | | Pre-calibrated smart optional lenses: 2x telephoto, wide angle | | Pre-calibrated smart optional lenses: 2x and 4x telephoto, wide angle | | - | | | | | |
| Wireless connectivity | - | | | | | | | Fluke Connect® app compatible. Wireless connectivity to PC, iPhone® and iPad® (iOS 4s and later), Android™ 4.3 and up, and WiFi to LAN ¹ | | | | | | | | | | |
| IR-Fusion* | AutoBlend™ mode, continuous blending | | | | | AutoBlend™ mode | | | | | | | | | | | | |
| Picture-In-Picture (PIP) | Picture-in-Picture | | | | | | | | | | | | | | | | | |
| Focus system | LaserSharp® Auto Focus, auto focus, manual focus, and EverSharp multifocal recording | | Auto focus, manual focus, and EverSharp multifocal recording | | MultiSharp™ Focus, LaserSharp® Auto Focus with built-in laser distance meter and advanced manual focus | | | | | | LaserSharp® Auto Focus with built-in laser distance meter and advanced manual focus | | Manual focus | Manual focus (TiS65), Fixed focus (TiS60) | Manual focus (TiS55), Fixed focus (TiS50) | Manual focus (TiS45), Fixed focus (TiS40) | Fixed focus | |
| Display | Extra-large 5.6 inch color TFT display, 1280 x 800 pixel resolution, suitable for daylight operation | | | 5.7 inch touchscreen LCD, 640 x 480 pixel resolution | | | | 3.5 inch touchscreen LCD, 640 x 480 pixel resolution | | | | 3.5 inch (landscape) 320 x 240 LCD | | | | | | |
| Design | Camcorder with handle, Tiltable LCoS color viewfinder display, 800 x 600 pixel resolution | | Camcorder | | Ergonomic design with a 240 degree rotating lens | | | | Rugged, ergonomic design for one-handed use | | | | Rugged, lightweight, ergonomic design for one-handed use | | | | | |
| Thermal sensitivity* | ≤ 0.05 °C at 30 °C target temp (50 mK) | ≤ 0.03 °C at 30 °C target temp (30 mK) | | ≤ 0.04 °C at 30 °C target temp (40 mK) | ≤ 0.05 °C at 30 °C target temp (50 mK) | ≤ 0.03 °C at 30 °C target temp (30 mK) | ≤ 0.04 °C at 30 °C target temp (40 mK) | ≤ 0.05 °C at 30 °C target temp (50 mK) | ≤ 0.05 °C at 30 °C target temp (50 mK) | ≤ 0.03 °C at 30 °C target temp (30 mK) | ≤ 0.05 °C at 30 °C target temp (50 mK) | | ≤ 0.08 °C at 30 °C target temp (80 mK) | | | ≤ 0.09 °C at 30 °C target temp (90 mK) | ≤ 0.10 °C at 30 °C target temp (100 mK) | ≤ 0.15 °C at 30 °C target temp (150 mK) |
| Temperature measurement range | -40 °C to +1200 °C (-40 °F to +2192 °F) High temperature option—request at time of order: up to 2000 °C (3632 °F) | | | -40 °C to +600 °C (-40 °F to +1112 °F) High temperature option—request at time of order: up to 2000 °C (3632 °F) | -20 °C to +800 °C (-4 °F to +1472 °F) | -20 °C to +1200 °C (-4 °F to +2192 °F) | -20 °C to +850 °C (-4 °F to +1562 °F) | -20 °C to +650 °C (-4 °F to +1202 °F) | -20 °C to +800 °C (-4 °F to 1472 °F) | -20 °C to +1200 °C (-4 °F to +2192 °F) | | -20 °C to +650 °C (-4 °F to +1202 °F) | -20 °C to +550 °C (-4 °F to +1022 °F) | -20 °C to +450 °C (-4 °F to +842 °F) | -20 °C to +350 °C (-4 °F to +662 °F) | -20 °C to +350 °C (-4 °F to +662 °F) | -20 °C to +250 °C (-4 °F to +482 °F) | |
| Frame rate | 30 Hz or 9 Hz versions | 60 Hz or 9 Hz versions | | 30 Hz or 9 Hz versions | 60 Hz or 9 Hz versions | | | | | | | | | | | | | |
| Subwindowing modes available: (add-on at time of order—subwindowing options are not available on 9 Hz models) | Option 1: 640 x 480 (60 fps) Option 2: 384 x 288 (120 fps) Option 3: 1024 x 96 (240 fps) | Option 1: 384 x 288 (120 fps) Option 2: 640 x 120 (240 fps) | | 384 x 288 (60 fps) | - | | | | | | | | | | | | | |
| Software | Fluke Connect® (web, mobile and SmartView® desktop) | | | | | | | | | | | | | | | | | |
| Voice annotation | 60 seconds maximum recording time per image, reviewable playback on camera; Bluetooth headset provided (where available) | | | | | | | 60 seconds maximum recording time per image; reviewable playback on camera; optional bluetooth headset available but not required | | | | 60 seconds maximum recording time per image, reviewable playback on camera; Bluetooth headset available separately (where available) | | | | | | |
| Text annotation | Yes | | | | | | | | | | | | | | | | | |
| Video recording | Standard and radiometric | | | | | | | | | | | | | | | | | |
| Streaming video (remote display) | Via HDMI; GigE Ethernet available in SmartView® software | | | Yes, see the live stream of the camera display on your PC, smartphone, or TV monitor. Via USB, WiFi hotspot, or WiFi network to Fluke Connect® SmartView® software on a PC; via WiFi hotspot to the Fluke Connect® app on a smartphone; or via HDMI to a TV monitor | | | | | | Yes, to Fluke Connect® SmartView® desktop software or mobile app | | | | - | | | | |
| Remote control operation | Yes | | | Yes, through Fluke Connect® SmartView® desktop software or mobile app | | - | | Yes, through Fluke Connect® SmartView® desktop software or mobile app | | | | - | | | | | | |
| Alarms | High temperature, low temperature, and isotherms (within range) | | | | | | | | | | | | | | | High temperature, low temperature | | |
| Warranty | Two-years (standard), extended warranties are available | | | | | | | | | | | | | | | | | |

*Best possible

¹Fluke Connect® not available in all countries.